



DuraFlash™

XL | CF 4.1 | CF Card

SMART's DuraFlash XL CF Cards offer reliable, high performance in an industry standard CompactFlash® (CF) form factor. The industrial-grade XL CF Card products specifically support OEM markets of networking, telecommunication and data communication, embedded computing, medical, and industrial applications. SMART has designed their CF Cards using Single-Level Cell (SLC) Flash technology for enhanced data integrity and life time expectations in critical embedded applications.

SMART's CF Card product line supports Self-Monitoring Analysis and Reporting Technology (S.M.A.R.T.), which is designed to reduce field failures and unscheduled service maintenance. S.M.A.R.T. enables a reliable monitoring application that efficiently supports CF Cards in the field and guarantees 24/7 service availability.

Features & Benefits

- Highly Reliable SLC NAND Flash Technology
- Static and Dynamic Wear-Leveling
- Field Upgradeable Firmware
- RoHS-6 Compliant
- Self-Monitoring Analysis and Reporting Technology (S.M.A.R.T.) Support

Product Family Overview

Capacity	Sequential Performance
XL CF 4.1 CF Card	
128MB to 8GB	Up to 30MB/s Read; Up to 12MB/s Write



Applications

- Communications
- Defense
- Gaming
- Industrial Control Equipment
- Networking
- Printers

Specifications

XL CF 4.1 CF Card	
NAND Type	SLC
Performance	
Sequential Read (maximum)	Up to 30MB/s
Sequential Write (maximum)	Up to 12MB/s
Reliability	
Data Reliability	< 1 Non-Recoverable Error in 10 ¹⁴ bits read
Data Retention	10 years >90% life remaining 1 year at the end of life
Endurance	TBW up to 3TB per 1GB capacity
Power	
VCC	5.0V+10% 3.3V+5%
Read	< 200mA
Write	< 200mA
Idle	< 4mA
Environmental	
Shock (operational)	50G @ 11ms
Vibration	15G peak to peak
Operating Temperature	Commercial: 0°C to +70°C Industrial: -40°C to +85°C
Storage Temperature	-55°C to +85°C
Humidity	5% to 95%
Physical	
Length	36.4mm
Width	42.8mm
Thickness	3.3mm

Ordering Information

Part Number	Density
XL CF 4.1 CF Card	
Commercial Operating Temperature (0°C to +70°C)	
SP9FD08GH3BACS02	8GB
SP9FD04GH3BACS02	4GB
SP9FD02GH3B8CS02	2GB
SP9FD02GH3BACS02	2GB
SP9FD01GH3B4CS02	1GB
SP9FD01GH3B8CS02	1GB
SP9FD512H3B2CS02	512MB
SP9FD512H3B4CS02	512MB
SP9FD256H3B1CS02	256MB
SP9FD256H3B2CS02	256MB
SP9FD128H3B1CS02	128MB
XL CF 4.1 CF Card	
Industrial Operating Temperature (-40°C to +85°C)	
SP9FD08GH3BAIS02	8GB
SP9FD04GH3BAIS02	4GB
SP9FD02GH3B8IS02	2GB
SP9FD02GH3BAIS02	2GB
SP9FD01GH3B4IS02	1GB
SP9FD01GH3B8IS02	1GB
SP9FD512H3B2IS02	512MB
SP9FD512H3B4IS02	512MB
SP9FD256H3B1IS02	256MB
SP9FD256H3B2IS02	256MB
SP9FD128H3B1IS02	128MB



For more information, please visit: www.smartm.com

*Product images are for promotional purposes only. Labels may not be representative of the actual product.

Headquarters/North America:

T: (+1) 800-956-7627 • T: (+1) 510-623-1231
F: (+1) 510-623-1434 • E: info@smartm.com

Latin America:

T: (+55) 11 4417-7200 • E: sales.br@smartm.com

Asia/Pacific:

T: (+65) 6678-7670 • E: sales.asia@smartm.com

EMEA:

T: (+44) 0 7826-064-745 • E: sales.euro@smartm.com

Customer Service:

T: (+1) 510-623-1231 • E: customers@smartm.com